



AT101

Fingertip Oximeter

The Lightest OLED Oximeter powered with only one AAA Battery



5-Directional Key



Ingress Protection



Graphic Color OLED



Micro-USB Port



Screen in 90°
180°270°360°



Alarm Function



Auto On/off



Powered by One Battery

Integrate all needs in “fingertip size”

AT101 orientates to adapt different users and fulfill all the needs within a compact size device. From the performance aspect, AT101 provides an accurate measurement result in seconds. In the same time, its versatile housing design can accommodate with the widest range of finger sizes from different populations. Furthermore, with combination of the latest electronics technology, AT101 is also presented with the most friendly interface to users and environments.

Product Features

► Simple operation

- Automatically turn on for immediate spot-checks;
- Color OLED and graphic display for conveniently viewing;
- Five directional keys for easy setting.

► Alarm

Adapt both audio and visual alarm for abnormal oximetry and pulse reading.

► Efficient power consumption

Extreme energy saving design and environment friendly.
(one AAA Alkaline battery for 18-hour continuous use)

► Built-in timer

Built-in stop watch function along with Spo2 measurement for breath counting or sporting usage.

Specifications

Models	AT101 I (Bluetooth)	AT101 B	AT101 C
Pulse Oximetry Range Resolution Accuracy Method	0% to 100% 1% 70% to 100% range: $\pm 2\%$; less than 70%: unspecified Dual wavelength LED		
Heart (Pulse) Rate Range Resolution Accuracy	30 to 250bpm 1bpm ± 1 bpm or $\pm 1\%$, whichever is greater		
Input & Output Auto on/off LCD display Input Key Alarm option Alarm setting	Whenever user inserts a finger, the device will turn on automatically. Vice versa, the device will turn off automatically, when the finger is removed from it. Full Color OLED A push-down key for interface operation A 5-directional key for interface operation A push-down key for interface operation Yes Yes No Low SpO2 alarm: setting range: 50%~ 95%; High SpO2 alarm: setting range: 80%~ 100%; Low heart rate alarm: setting range: 30BPM ~ 110BPM; High heart rate alarm: setting range: 75BPM ~ 250BPM		
Mechanical Weight Size	Without battery: < 26g (0,92 ounces) L67.5mm(2.63") x W38mm(1.48") x H25mm(0.98")		
Battery Type Usage life	1 AAA Alkaline battery Auto on/off features , >18-hour typical operation		
Environmental Operating Temperature Storage Temperature Humidity Atmospheric Pressure	5° to 40° C; 41° F to 104° F -30° to 70° C; -22° to 158° F 10% to 90%, non-condensing for both operating & storage 700 hPa ~ 1013 hPa for both operating and storage		
Classification Degree of Protection Ingress Protection Mode of operation Safety EMC Performance standard	Type BF Applied part IP22 Continuous use Continuous use Spot Check IEC60601-1 IEC60601-1-2 ISO80601-2-61		
Standard Package Package Dimension Accessories Optional Accessories	L75mm(2.95") x W60mm(2.36") x H35mm(1.38") User manual X 1, AAA battery X 1 Neck Strap (Black); Belt pouch (Black)		
Wireless connection	Bluetooth 4.0 BLE	N/A	N/A

