OMRON

Find out more

www.omronhealthcare-ap.com/sg

MRON Healthcare Singapore

THE OMRON PROMISE: • SAFETY • QUALITY • EASE OF USE

IF IT MATTERS TO YOU, IT MATTERS TO US.

SPECIFICATIONS

Model (code)	MICRO A-I-R U100 (NE-U100-E)
Rating	100-240V 50/60Hz (Optional AC adapter) 3 VDC (two batteries/Type AA/LR6)
Power Consumption	Approx. 1.2 W
Residual Volume	Approx. 0.5 ml
Battery Life	Approx. 4 hours
Operating Temperature/ Humidity/Air Pressure	+10°C to +40°C, 30 to 85%RH (non-condensing), 800 - 1060hPa
Storage and Transport Temperature/Humidity	-20°C to +60°C, 10 to 90%RH (non-condensing)
Weight	Approx. 200g (excl. batteries)
Dimensions	Approx. 45 (W) x 130 (H) x 60 (D) mm (Main Unit assembled with Medication Container and Mask Adapter)
Contents	Main Unit, Main Unit Cover, Medication Container, Mesh Cap, Mask Adapter, Mouthpiece, 2 Batteries (AA/LR6), Adult Mask (PVC), Child Mask (PVC), Soft Pouch, Instruction Manual, Quick Setup Guide



OMRON HEALTHCARE Co., Ltd.

53, Kunotsubo, Terado-cho, Muko, KYOTO, 617-0002 JAPAN

Asia Pacific HQ
OMRON HEALTHCARE SINGAPORE PTE LTD.

438A Alexandra Road, #05-05/08 Alexandra Technopark, Singapore 119967 www.omronhealthcare-ap.com EC REP

OMRON HEALTHCARE EUROPE B.V. Scorpius 33, 2132 LR Hoofddorp,

Scorpius 33, 2132 LR Hoofddorp, THE NETHERLANDS

Production Facility
OMRON HEALTHCARE CO., LTD.
Matsusaka Factory
Mie, JAPAN

C€0197



OMRON'S PROMISE FOR EASE OF USE









PORTABLE NEBULIZER

Battery operated and pocket-sized, the nebulizer enables your medication to be taken while you are out and about.



Т

DISCREET TREATMENTS, ANYWHERE

The silent feature of the MICRO A-I-R NE-U100 makes it the ideal device for administering medication any time, anywhere.







SMALLER PARTICLE SIZE, GREATER ABSORPTION

With the advanced vibrating mesh technology, the nebulizer produces an average particle size of 4.5 microns (µm) for effective absorption in the lower airways.



360° USABILITY

360° OPERATION

The MICRO A-I-R NE-U100 has a unique 360° design that allows for use in any position without spillage.

